

ELECTRIC DRAIN SNAKE OPERATION GUIDE

1. Before stepping on the foot pedal, place the guide tube and cable into the drain opening.
2. Tighten the knob at the top of the power cable feed so that the feed roller presses against the cable.
3. The feed lever has 3 positions: **Push down** for the cable to feed forward, **pull all the way up** for cable to reverse and put lever in the **middle** for a neutral position.
4. Move the motor switch on the back of the unit to the “forward” position.
5. With a gloved hand on the guide tube, step on the air foot pedal to start the machine. Feed the cable into the line. Adjust the feeding rate to the resistance met. **DO NOT FORCE THE CABLE.**
6. If the cable starts to buckle or twist, release pressure on the foot pedal. Move the feed lever up and step on the foot pedal to retract excess cable back into the drum, then continue.

7. If you're having trouble getting around tight bends, try putting the machine in reverse for several seconds while applying steady pressure.
8. When the cable reaches the stoppage, move the feed lever toward neutral to allow the cable to progress forward slowly, chewing into the stoppage as it goes.
9. After the line has been opened, retract the cable by moving the feed lever up. Make sure the motor switch is in the forward position.

HELPFUL TIPS

- **Do not** let the cutter get caught in the stoppage. It can cause kinking and breaking of the cable which is **not covered under the damage waiver.**
- Be sure to wear leather gloves when operating. **DO NOT** wear rubber gloves as they will get stuck/caught on the cable.