

Operating Instructions



6' Propane Lava Grill

Note: Always follow all safety instructions affixed to this grill. Follow all local codes when using this grill.

Operating Instructions

- Remove cover or open hood before lighting.
- Connect regulator, check for leaks, open tank valve fully, and allow system to pressurize.
- Ignite burners with a long lighter/match, then adjust knobs for desired temperature (~800°F in 5–8 min).
- Shut down by turning control knobs **off first**, then closing the tank valve.

Troubleshooting

- Common issues: burners not lighting, grill shutting off, frozen regulator.
- Most fixes involve resetting valves, leak-checking, or ensuring proper propane tank size.
- Frozen regulator can be caused by undersized tanks or moisture in fuel—purge/refill if necessary.

Note: On average, you will use 2 pounds of propane per burner per hour.

To shut down:

1. Turn all knobs clockwise to the “off” position.
2. Shut off the main gas or close tank valves.
3. Disconnect propane.

Caution:

- **For outdoor use only** in well-ventilated areas.
- Never use or store propane cylinders indoors or near flammable materials.
- Use only manufacturer-supplied hose, regulator, and lava rock.
- Keep combustible materials at least 12 inches away.
- Keep children and pets away when in use.
- Always check for gas leaks before operation using a **soapy water test**—never a flame.

For any questions or concerns, be sure to contact us immediately.

Thank you for your business!

1155 Route 9
Wappingers Falls, NY
(845) 298-0011



1 Precision Road
Danbury, CT
(203) 744-2295